




40 Sycamore Road,
Rathnapish,
Carlow,
Ireland.

Tel: 059 9131725
M: 087 9894696

www.foleysoundengineering.com
info@foleysoundengineering.com

PRODUCT	PRODUCT REF	DESCRIPTION
COMMERCIAL SERIES PROCESSORS		
	JBL1137	CSM-32 Affordable, professional public address processor and zone mixer. Digital processor with analogue-style control. Quick and simple configuration via front & rear panel controls. Three stereo line inputs and one mic input. One line input for priority audio. Two stereo outputs with dedicated subwoofer output. One mono isolated output for music-on-hold system. Music EQ per zone, global mic EQ. AutoWarmth™ and LevelGuard™. Two Zone Remote ports for connection to optional CSR controllers. Contact Closure control. Link bus for input sharing. Security plate for front panel lockout included.
	JBL1136	CSM-21 Affordable, professional public address processor and zone mixer. Digital processor with analogue-style control. Quick and simple configuration via front & rear panel controls. Two stereo line inputs and one mic input. One line input for priority audio. One stereo output with dedicated subwoofer output. Music EQ and global mic EQ. AutoWarmth™ and LevelGuard™. One Zone Remote port for connection to optional CSR controller. Contact Closure control. Link bus for input sharing. Security plate for front panel lockout included.
	JBL1172	CSA-2120 Professional grade two channel amplifier built for installed sound applications. 2x120W at 4/8 ohms. Convection cooled. Audio standby energy saving mode. Summing RCA inputs for each channel. Switched mode universal power supply.
	JBL1195	CST 2120 TRANSFORMER KIT Transformer module provides impedance and voltage matching for the CSA-2120 amplifier to drive 70V and 100V distributed speaker systems.
	JBL1375	CSMA-180 Commercial Series mixer-amplifier utilising Crown's DriveCore technology. 4 inputs with 1 80W output. Can drive 8 & 4 ohm loads and 70/100V lines without need for a separate transformer. Ideal for commercial and industrial use. Fanless, space-saving 1U design. Sleek industrial look with illuminated rings, making them easy to see and operate. Euro-block type mic/line input connectors and output connectors. Independent Bass and Treble controls for each output channel. RJ45 connectors for use with CSR-V in-wall controllers.
	JBL1376	CSMA-1120 As above with 120W amplifier section.

PRODUCT	PRODUCT REF	DESCRIPTION
COMMERCIAL SERIES PROCESSORS		
	JBL1377	CSMA-240 Commercial Series mixer-amplifier utilising Crown's DriveCore technology. 8 inputs with two 40W outputs. Can drive 8 & 4 ohm loads and 70/100V lines without need for a separate transformer. Ideal for commercial and industrial use. Fanless, space-saving 1U design. Sleek industrial look with illuminated rings, making them easy to see and operate. Euro-block type mic/line input connectors and output connectors. Configurable output routing. Independent Bass and Treble controls for each output channel. RJ45 connectors for use with CSR-V in-wall controllers.
	JBL1378	CSMA-280 As above with 2x 80W outputs.
	JBL1379	CSMA-2120 As above with 2x 120W outputs.
		CSR-V Remote volume controller for the CSM processors. Connection is via Cat5 cable with universally accepted RJ45 connectors with a maximum cable length of 1000ft. Mounts in a standard light switch wallbox. Available in black or white.
	JBL1138	CSR-V-BLK
	JBL1139	CSR-V-WHT
		CSR-2SV Remote volume and source controller for the CSM-21 processor. Connection is via Cat5 cable with universally accepted RJ45 connectors with a maximum cable length of 1000ft. Mounts in a standard light switch wallbox. Available in black or white.
	JBL1140	CSR-2SV-BLK
	JBL1141	CSR-2SV-WHT
		CSR-3SV Remote volume and source controller for the CSM-32 processor. Connection is via Cat5 cable with universally accepted RJ45 connectors with a maximum cable length of 1000ft. Mounts in a standard light switch wallbox. Available in black or white.
	JBL1142	CSR-3SV-BLK
	JBL1143	CSR-3SV-WHT

PRODUCT	PRODUCT REF	DESCRIPTION
COMMERCIAL SERIES PROCESSORS		
	JBL1144	CSPM-1 The JBL Commercial® CSPM series microphones are dynamic closetalking microphones for paging systems in bars/pubs, theatre lobbies, department stores, and more. Paging for one zone, ideal for the CSM-21. Momentary push-to-talk button.
	JBL1145	CSPM-2 The JBL Commercial® CSPM series microphones are dynamic closetalking microphones for paging systems in bars/pubs, theatre lobbies, department stores, and more. Provides paging for two zones, making it ideal for the CSM-32. Two latching buttons for zone selection and one momentary PTT button.
	JBL1146	CSPM-4 The JBL Commercial® CSPM series microphones are dynamic closetalking microphones for paging systems in bars/pubs, theatre lobbies, department stores, and more. Provides paging for four zones, for use with two CSM-32 devices linked together. Four latching buttons for zone selection and one momentary PTT button.
COMMERCIAL SERIES LOUDSPEAKERS		
	JBL1147	CSS-1S/T Compact 2-way wall-mount loudspeaker for use on 100V/70V distributed line systems with taps at 10W, 5W & 2.5W (70v only), or 60W 8Ω direct mode. 5.25" LF loudspeaker and 0.75" tweeter provide full-range sound quality for foreground or background music and are voiced for maximum speech clarity and intelligibility. 86dB sensitivity. Includes wall-mounting bracket.
	JBL1098	CSS8004 Affordable ceiling loudspeaker for paging and background music applications. 4" speaker. High 90dB sensitivity. 5 W multi-tap transformer for 100V, 70V and 25V distributed lines. Very wide 175° coverage. Fits CCS-BB4 backcan.
	JBL1099	CSS8008 Affordable ceiling loudspeaker for paging and background music applications. 8" speaker. High 96dB sensitivity. 5 W multi-tap transformer for 100V, 70V and 25V distributed lines. 120° conical coverage. Fits CCS-BB8 backcan.
	JBL1100	CSS8018 Affordable high output ceiling loudspeaker for paging and background music applications. 8" speaker. Very high 97dB sensitivity. 10 W multi-tap transformer for 100V, 70V and 25V distributed lines. Fits CCS-BB8 backcan.

PRODUCT	PRODUCT REF	DESCRIPTION
COMMERCIAL SERIES LOUDSPEAKERS		
	JBL1101	CSS-BB4x6 4" backcan for CSS8004. Zinc-plated, power-coated steel.
	JBL1102	CSS-BB8x6 8" backcan for CSS8008 and CSS8018. Zinc-plated, power-coated steel.
	JBL1103	CSS-TR4/8x12 Tile rails for CSS-BB4x6 and CSS-BB8x6 backcans.
8100 SERIES		
	JBL0784	8124 4" open-backed ceiling speaker. 70/100V transformer with taps at 6W, 3W, 1.5W (plus 0.75W at 70V only). 93dB sensitivity, 60Hz-18kHz frequency response for non-plenum applications. Priced as each, sold in packages of four pieces.
	JBL0783	8128 8" open-backed ceiling speaker. 70/100V transformer with taps at 6W, 3W, 1.5W (plus 0.75W at 70V only). 97dB sensitivity, 50Hz-16kHz frequency response for non-plenum applications. Priced as each, sold in packages of four pieces.
	JBL0888	8138 8" ceiling speaker for pre-install backcan. 70/100V transformer with taps at 6W, 3W, 1.5W (plus 0.75W at 70V only). 97dB sensitivity, 90Hz-18kHz frequency response. 90° coverage. Priced as each, sold in packages of four pieces.
	JBL0793	MTC-8124C C-ring for 8124. With integral clips for optional tile rails. Four pieces.
	JBL0794	MTC-8128C C-ring for 8128. With integral clips for optional tile rails. Four pieces.
	JBL0889	MTC-81BB8 Pre-install backcan for 8138. 7.4 litre volume. Priced as each, sold in packages of four pieces.
	JBL0890	MTC-81TB8 Tile bridge for 8138. 19 gauge steel with e-coated finish. Priced as each, sold in packages of four pieces.
	JBL0795	MTC-RAIL Rail support for tile ceiling. 4 per pack. 2 required per speaker.

PRODUCT	PRODUCT REF	DESCRIPTION
CONTROL CONTRACTOR		
		CONTROL 19 CS 8" ceiling subwoofer. Nested chamber design. Linear aperture port. 42Hz-200Hz. 200W program, 100W pink noise capacity. SonicGuard overload protection. With backcan, support plate and rails. Priced as each, sold as pairs. Optional new construction bracket (MTC-19NC) and mud plaster ring bracket (MTC-19MR).
	JBL0091	CONTROL 19 CS
	JBL0173	MTC19-NC
	JBL0172	MTC19-MR
	JBL0092	CONTROL 19 CST As above with transformer for 70V or 100V line. Taps at 60W, 30W and 15W. No SonicGuard. Priced as each, sold as pairs.
		CONTROL 24C 4" two-way vented ceiling speaker. 80Hz-20kHz, 86dB sensitivity. 80W program, 40W pink noise capacity. SonicGuard overload protection. 130° coverage. With backcan, grille, support plate and tile rails. Priced as each, sold as pairs. Optional new construction bracket (MTC-24NC), mud plaster ring bracket (MTC-24MR) and trim ring for retrofit in 250mm cutouts (MTC-24TR)
	JBL0097	CONTROL 24C
	JBL0188	MTC-24NC
	JBL0187	MTC-24MR
	JBL0189	MTC-24TR
		Control 24 CT As above with transformer for 70V or 100V line. Taps at 30W, 15W and 7.5W. Priced as each, sold as pairs. Black or white.
	JBL0099	CONTROL 24 CT
	JBL0933	CONTROL 24 CT - BK
	JBL0098	Control 24 C MICRO 4" two-way ceiling speaker. 30W program, 15W pink noise capacity. Extremely wide 150° coverage. With backcan, grille, support plate and tile rails. Priced as each, sold as pairs.
	JBL0100	Control 24 CT MICRO As above with transformer for 70V or 100V line. Taps at 8W, 4W, 2W and 1W. Priced as each, sold as pairs.

PRODUCT	PRODUCT REF	DESCRIPTION
CONTROL CONTRACTOR		
	JBL0780	Control 24 CT MICRO+ Complete assembly with backcan, grille, support plate and tile rails. 70/100V transformer taps at 25W and 12.5W 150° coverage. 100mm depth. Priced as each, sold as pairs.
		CONTROL 26C 6.5" two-way ceiling speaker. 75Hz-20kHz, 89dB sensitivity. 150W program, 75W pink noise capacity. SonicGuard overload protection. 16 ohms. With backcan, grille, support plate and tile rails. Priced as each, sold as pairs. Optional new construction bracket (MTC-26NC), mud plaster ring bracket (MTC-26MR) and trim ring for retrofit in 250mm cutouts (MTC-26TR).
	JBL0108	CONTROL 26C
	JBL0198	MTC-26NC
	JBL0197	MTC-26MR
	JBL0199	MTC-26TR
	JBL0109	CONTROL 26 CT As above with transformer for 70V or 100V line. Taps at 60W, 30W and 15W. No SonicGuard. Priced as each, sold as pairs.
	JBL1148	CONTROL 26 CT-LS As above but UL1480 listed for use in Fire Alarm and/or Emergency Communications systems. Priced as each, sold as pairs.
	JBL0107	CONTROL 26 DT Compact ceiling speaker assembly configured to install into standard ceiling backcans designed for 8" drivers. Coaxial woofer with long-life butyl rubber surround and titanium coated tweeter. 70/100V transformer with taps at 60W, 30W and 15W. Priced as each, sold as pairs.
	JBL1215	MTC-48TRx12 4x4-foot tile rail. Compatible with 8100 series, Control 19, all Control 24 & 26 models, Control 40 series and Control 226C/T.

PRODUCT	PRODUCT REF	DESCRIPTION
CONTROL CONTRACTOR WALL MOUNT SERIES		
		CONTROL 23 3.5" two-way vented wall-mounted speaker. Invisiball® installation system. 50W program power, 8 ohms. Also available as Control 23T with 70/100V transformer with single tap at 10W (100V), 5W (70V). Black or white. Priced as each, sold in pairs.
	JBL0093	CONTROL 23
	JBL0094	CONTROL 23 WH
	JBL0095	CONTROL 23 T
	JBL0096	CONTROL 23 T WH
		CONTROL 25 5.5" two-way vented wall-mounted speaker. Invisiball® installation system. 150W program power, 8 ohms. Also available as Control 25T with 70/100V transformer with taps at 30W, 15W and 7.5W (plus 3.7W at 70V only). Black or white. Priced as each, sold in pairs.
	JBL0101	CONTROL 25
	JBL0121	CONTROL 25 WH
	JBL0105	CONTROL 25 T
	JBL0120	CONTROL 25 T WH
		CONTROL 25 AV 5.5" two-way shielded wall-mounted speaker. Weather resistant indoor/outdoor steel grille. Invisiball® installation system. 200W program power, 8 ohms and 70/100V transformer with taps at 60W, 30W and 15W (plus 7.5W at 70V only). Includes MTC-PC sealed-entrance panel cover. Black or white. Priced as each, sold in pairs. LS version is UL 1480 UUMW listed for Fire Alarm and/or emergency communications systems.
	JBL0103	CONTROL 25 AV
	JBL0104	CONTROL 25 AV WH
	JBL0934	CONTROL 25 AV LS
	JBL0935	CONTROL 25 AV LS WH
		CONTROL 28 8" two-way vented wall-mounted speaker. Invisiball® installation system. 175W program power, 8 ohms. Also available as Control 28T-60 with 70/100V transformer with taps at 60W, 30W and 15W (plus 7.5W at 70V only). Black or white. Priced as each, sold in pairs.
	JBL0110	CONTROL 28
	JBL0111	CONTROL 28 WH
	JBL0112	CONTROL 28 T 60
	JBL0113	CONTROL 28 T 60 WH

PRODUCT	PRODUCT REF	DESCRIPTION
CONTROL CONTRACTOR WALL MOUNT SERIES		
		CONTROL 29 AV 1 High output 8" indoor/outdoor speaker. 300W program power, 92dB sensitivity. 70/100V transformer with taps at 110W, 55W and 28W (plus 14W at 70V only). 110°x80° coverage with rotatable horn. Invisiball® installation system plus ten M6 suspension points. Kevlar cone woofer and titanium compression driver. Includes SonicGuard overload protection and MTC-PC2 sealed entrance panel cover. Black or white
	JBL0628	CONTROL 29 AV 1
	JBL0632	CONTROL 29 AV 1 WH
		CONTROL 30 10" high output indoor/outdoor speaker 38Hz-17kHz frequency response. 250W program power, 92dB sensitivity. 8 ohms plus 70/100V transformer with taps at 150W, 75W and 38W (plus 19W at 70V only). Invisiball® installation system plus ten M6 suspension points and optional U-bracket. Includes SonicGuard overload protection. Black or white.
	JBL0628	CONTROL 30
	JBL0632	CONTROL 30 WH
		CONTROL SB-2 Slot-loaded vented bandpass subwoofer. Dual 10" voice coil transducers. Trapezoidal enclosure for corner placement. 38Hz-160Hz. 340W program power. 100dB sensitivity. 8 ohm stereo with high-pass satellite outputs
	JBL0086	CONTROL SB-2
		CONTROL SB-210 Low-profile, high power subwoofer. Dual 10" aluminium/ceramic composite cone drivers. 42Hz-200Hz frequency response. 400W program power. Fully outdoor capable (IP-x5). SonicGuard overload protection. 13 M6 suspension points. Optional U-bracket. Black or white.
	JBL0087	CONTROL SB-210
	JBL0088	CONTROL SB-210 WH
	JBL0175	MTC-SB210T
	JBL0815	MTC-SB210-SAT
	JBL0176	MTC-SB210T-SAT
		MTC-23V Vertical array bracket for two Control 23 speakers.
	JBL0184	MTC-23V

PRODUCT	PRODUCT REF	DESCRIPTION
		CONTROL CONTRACTOR WALL MOUNT SERIES
		MTC-23CM Ceiling mount adaptor for Control 23. Two pieces. Black or white.
	JBL0179	MTC-23CM
	JBL0180	MTC-23CM WH
		MTC-23SSG Stainless steel grille for Control 23 models. Silver, black or white.
	JBL0181	MTC-23SSG
	JBL0182	MTC-23SSG-BK
	JBL0183	MTC-23SSG-WH
		MTC-23WMG WeatherMax replacement grille for Control 23 models. Black or white.
	JBL0185	MTC-23WMG
	JBL0186	MTC-23WMG WH
		MTC-25V Vertical array bracket for two Control 25 speakers.
	JBL0194	MTC-25V
		MTC-23/25H Horizontal array bracket for two Control 23 or Control 25. 60° splay. Three brackets connect to form suspendable assembly for three or six speakers, providing 360° coverage.
	JBL0190	MTC-23/25H
		MTC-25SSG Stainless steel grille for Control 25 models. Silver, black or white.
	JBL0191	MTC-25SSG
	JBL0192	MTC-25SSG BK
	JBL0193	MTC-25SSG WH
		MTC-25WMG WeatherMax replacement grille for Control 25 models. Black or white.
	JBL0195	MTC-25WMG
	JBL0196	MTC-25WMG WH

PRODUCT	PRODUCT REF	DESCRIPTION
CONTROL CONTRACTOR WALL MOUNT SERIES		
		MTC-28V Vertical array bracket for two Control 28 speakers.
	JBL0206	MTC-28V
		MTC-28H Horizontal array bracket for two Control 28. 60° splay. Three brackets connect to form suspendable assembly for three or six speakers, providing 360° coverage.
	JBL0202	MTC-28H
		MTC-28/25CM Ceiling mount adaptor for Control 25 & 28. Two pieces. Black or white.
	JBL0200	MTC-28/25CM
	JBL0201	MTC-28/25CM WH
		MTC-28SSG Stainless steel grille for Control 28 models. Silver, black or white.
	JBL0203	MTC-28SSG
	JBL0204	MTC-28SSG BK
	JBL0205	MTC-28SSG WH
		MTC-28WMG WeatherMax replacement grille for Control 28 models. Black or white.
	JBL0207	MTC-28WMG
	JBL0208	MTC-28WMG WH
		MTC-29CM Ceiling mount adaptor for Control 29AV. Two pieces. Black or white.
	JBL0209	MTC-29CM
	JBL0210	MTC-29CM WH
		MTC-29UB U-bracket for Control 29AV. Black or white.
	JBL0211	MTC-29UB
	JBL0212	MTC-29UB WH
		MTC-30CM Ceiling mount adaptor for Control 30. Two pieces. Black or white.
	JBL0213	MTC-30CM
	JBL0214	MTC-30CM WH

PRODUCT	PRODUCT REF	DESCRIPTION
CONTROL CONTRACTOR WALL MOUNT SERIES		
		MTC-30MK-WH Marine grille kit for Control 30. Consists of grille, new seals and stainless steel screws
	JBL1268	MTC-30MK-WH
		MTC-30UB U-bracket for Control 30. Black or white.
	JBL0215	MTC-30UB
	JBL0216	MTC-30UB WH
		MTC-SB2W Wall/corner bracket for Control SB2.
	JBL0170	MTC-SB2W
		MTC-SB2C Ceiling bracket for Control SB2.
	JBL0169	MTC-SB2C
		MTC-210UB U-Bracket for Control SB-210. Black or white.
	JBL0177	MTC-210UB
	JBL0178	MTC-210UB WH
		MTC-PC2 Panel cover. Liquid-tight seal for input terminals, also functions as strain relief. Fits all surface models. Pack of two pieces.
	JBL0782	MTC-PC2
CONTROL CONTRACTOR IN-WALL SPEAKERS		
		Control 126W Premium in-wall loudspeaker. Two-way with 6.5" woofer and titanium tweeter. High-slope crossover network. 100W program power (50W RMS), 88dB sensitivity. 38Hz-20kHz frequency response. 98mm depth. Paintable. Also available as Control 126WT with 70/100V transformer. Taps at 30W, 15W and 7.5W (plus 3.7W at 70V only). Priced as each, sold in pairs.
	JBL0586	Control 126W
	JBL0606	Control 126WT
		MTC-126RIF Rough in frame for installing Control 126 to studs in new construction. Priced as each, sold in pairs.
	JBL0638	MTC-126RIF

PRODUCT	PRODUCT REF	DESCRIPTION
CONTROL CONTRACTOR IN-WALL SPEAKERS		
		Control 128W Premium in-wall loudspeaker. Two-way with 8" woofer and titanium tweeter. High-slope crossover network. 120W program power (60W RMS), 90dB sensitivity. 30Hz-20kHz frequency response. 102mm depth. Paintable. Also available as Control 128WT with 70/100V transformer. Taps at 50W, 25W and 12W (plus 6W at 70V only). Priced as each, sold in pairs.
	JBL0587	Control 128W
	JBL0607	Control 128WT
		MTC-128RIF Rough in frame for installing Control 128 to studs in new construction. Priced as each, sold in pairs.
	JBL0646	MTC-128RIF
CONTROL 10 SERIES		
		Control 12 C/T Full-range ceiling speaker consisting of a 3" wide-bandwidth cone driver mounted in a vented, paintable baffle with a preattached blind-mount backcan for quick and easy installation. Dual conduit/cable clamps. Combined 70V/100V and low impedance direct operation. 20 Watts at 8Ω nominal setting. 15W multi-tap at 70V/100V. 68 Hz – 17 kHz bandwidth with wide 130° coverage. White or black (-BK). Price individually, packaged in pairs.
	JBL01345	Control 12 C/T
	JBL01346	Control 12 C/T -BK
		Control 14 C/T Full-range ceiling speaker with a 4 " high tech cone driver and a 19 mm softdome liquid cooled tweeter mounted in a vented, paintable baffle with a pre-attached blind-mount backcan for quick and easy installation. Dual conduit/ cable clamps. Combined 70V/100V and low impedance direct operation. 30 Watts at 8Ω nominal setting. 25W multi-tap at 70V/100V. 74 Hz – 20 kHz bandwidth with wide 120° coverage. White or black (-BK). Price individually, packaged in pairs.
	JBL01347	Control 14 C/T
	JBL01348	Control 14 C/T -BK

PRODUCT	PRODUCT REF	DESCRIPTION
CONTROL 10 SERIES		
		Control 16 C/T Full-range ceiling speaker with a 6.5" high tech cone driver and a 19 mm soft-dome liquid cooled tweeter mounted in a vented, paintable baffle with a pre-attached blind-mount backcan for quick and easy installation. Dual conduit/cable clamps. Combined 70V/100V and low impedance direct operation. 50 Watts at 8Ω nominal setting. 30W multi-tap at 70V/100V. 62 Hz – 20 kHz bandwidth with wide 110° coverage. High 91 dB sensitivity for high maximum SPL. White or black (-BK). Price individually, packaged in pairs.
	JBL01349	Control 16 C/T
	JBL01350	Control 16 C/T -BK
CONTROL 200 SERIES		
		Control 226 C/T 6.5" coax ceiling speaker. 120° coverage. 150W. 47Hz-19kHz frequency response. 90dB sensitivity. 1" exit compression driver. 8 ohms plus 70/100V transformer with taps at 60W, 30W and 15W. 13" rounded ported baffle. Priced as each, sold as pairs.
	JBL0728	Control 226 C/T
		Control 227 6.5" coax ceiling speaker with HF driver. 120° coverage. 150W power handling. Coaxial design with kevlar reinforced 6.5" woofer and 1" compression driver. Extraordinary clarity for speech and vocals. Integrated backcan with clean contemporary grille sold separately. Also available with 70/100V transformer with 60W tap (Control 227CT).
	JBL0730	Control 227C
	JBL0731	Control 227CT
		MTC-200BB6 Cylindrical backcan for Control 227 C & C/T. 16 gauge metal construction lined with 12 mm MDF.
	JBL0734	MTC-200BB6
		MTC-RG6/8 Round grille for Control 328 and Control 227.
	JBL0732	MTC-RG6/8
		MTC-SG6/8 Square grille for Control 328 and Control 227.
	JBL1265	MTC-SG6/8

PRODUCT	PRODUCT REF	DESCRIPTION
CONTROL 200 SERIES		
		MTC-TB6/8 Tile bridge for suspended ceiling install.
	JBL0733	MTC-TB6/8
		MTC-TCD Thick-ceiling dog-ears.
	JBL1276	MTC-TCD
		MTC-300T150 Optional 150W transformer for 227C.
	JBL0653	MTC-300T150
CONTROL 300 SERIES		
		Control 321 12" premium coax ceiling speaker. 90° coverage. 250W power handling. 34Hz-to 18kHz frequency response. 94dB sensitivity. 2124H compression driver. 14.3" square ported baffle, 9" deep. EZ-Rail for ease of installation. Also available as Control 321CT with 70/100V multi-tap transformer. Taps at 60W, 30W and 15W (plus 7.5W at 70V only).
	JBL0639	Control 321C
	JBL0640	Control 321CT
		Control 322 12" ceiling speaker with medium format compression driver. 90° coverage. 400W power handling. 32Hz-to 20kHz frequency response. 95dB sensitivity. 2407H compression driver. 14.3" square ported baffle, 9" deep. EZ-Rail for ease of installation. Also available as 322CT with 70/100V multi-tap transformer. Taps at 100W, 50W and 25W (plus 12.5W at 70V only).
	JBL0641	Control 322C
	JBL0642	Control 322CT
		Control 312CS 12" ceiling subwoofer. 400W power handling. 30Hz-to 4.5kHz frequency response. 92dB sensitivity. 14.3" square ported baffle, 9" deep. EZ-Rail for ease of installation.
	JBL0645	Control 312CS

PRODUCT	PRODUCT REF	DESCRIPTION
CONTROL 300 SERIES		
		Control 328C 8" coax ceiling speaker with 12" waveguide. 100° coverage. 250W power handling. 45Hz-to 18kHz frequency response. 93dB sensitivity. 2412H compression driver. 11.8" rounded ported baffle/waveguide, 6.4" deep. Also available as Control 328CT with 70/100V multi-tap transformer. Taps at 60W, 30W and 15W (plus 7.5.5W at 70V only). Depth 8.8".
	JBL0643	Control 328C
	JBL0644	Control 328CT
		MTC-300BB8 Backcan for Control 328. 16 gauge metal construction lined with heavy duty MDF. 15" diameter x 10.6" deep.
	JBL0649	MTC-300BB8
		MTC-300BB12 Backcan for 12" models. 16 gauge metal construction lined with heavy duty MDF. 23" x 18" x 12.8".
	JBL0650	MTC-300BB12
		MTC-300SG12 Square white metal grille for 12" models.
	JBL0652	MTC-300SG12
CONTROL 40 SERIES		
		Control 47C/T Wide coverage, extended bass ceiling speaker featuring conical RBI technology. 6.5" two-way. 120° consistent coverage. 50Hz-20kHz. 150W program and 75W pink noise capacity. 70/100V taps at 60W, 30W and 15W. Also available as Control 47LP-PL low profile at 142mm deep. 68Hz-20kHz. Priced as each, sold as pairs.
	JBL0785	Control 47C/T
	JBL0786	Control 47LP
	JBL1271	MTC-47MR
	JBL1272	MTC47-NC
		Control 47HC High ceiling, narrow coverage speaker featuring conical RBI technology. Specs as Control 47C/T-PL above but with 75° coverage. 55Hz-20kHz. Priced as each, sold as pairs.
	JBL0787	Control 47HC

PRODUCT	PRODUCT REF	DESCRIPTION
CONTROL 40 SERIES		
		Control 40 CS/T Direct radiating in-ceiling subwoofer. Long throw 8" driver. 30Hz-280Hz. 200W program, 100W pink noise capacity. 70/100V transformer with taps at 60W, 30W and 15W. Built-in crossover network with outputs for 2 or 4 Control 42C satellite speakers. Priced as each, sold as pairs.
	JBL0789	Control 40 CS/T
		Control 42C Ultra-compact satellite speaker for use with Control 40 CS/T subwoofer. 160Hz-20kHz. 82dB sensitivity. 30W program, 15W pink noise. C-ring and tile rails optional. Priced as each, sold as pairs.
	JBL0788	Control 42C
	JBL1269	MTC-42MR
	JBL1270	MTC42-NC
CONTROL CONTRACTOR 50 SERIES		
		Control 50S/T Compact surface-mount subwoofer. 8" long-throw woofer. 100W continuous (400W peak). Selectable 70/100V or low impedance input. Built-in crossover network, drives 2 or 4 satellite speakers. Wall mount bracket included. Black or white.
	JBL0878	Control 50S/T
	JBL0879	Control 50S/T WH
		Control 52 Satellite speaker for use with Control 50S/T or Control 40CS/T subwoofers. 2.5" low-distortion driver. Wall mount bracket included. Black or White. Priced individually, sold as pairs.
	JBL0880	Control 52 S/T
	JBL0881	Control 52S/T WH
		C50PACK Subwoofer/satellite system, consisting of 1x Control 50S/T and 4x Control 52. Black or white.
	JBL0882	C50PACK
	JBL0883	C50PACK-WH

PRODUCT	PRODUCT REF	DESCRIPTION
CONTROL CONTRACTOR 60 SERIES		
		Control 62P Ultra-compact mid-high satellite pendant speaker. 2" driver. 20 Watts, 16 ohms. Can intermix with Control 52 surface mount and Control 42C in-ceiling speakers. For full-range, wide bandwidth performance, up to 4 pieces can be driven from a Control 50S/T or Control 40CS/T subwoofer. Available in black or white.
	JBL1090	CONTROL 62P
	JBL1091	CONTROL 62P WH
		Control 65P/T Compact full-range pendant speaker. Incorporates JBL' exclusive Radiation Boundary Integration (RBI) technology to provide very consistent, wide coverage. 120° conical coverage. 5.25" LF driver with silk-dome tweeter. 75 watts. 8 ohms and 60W multi-tap transformer. Available in black or white.
	JBL1092	CONTROL 62P/T
	JBL1093	CONTROL 62P/T WH
		Control 67P/T Extended range full-range pendant speaker. Incorporates JBL' exclusive Radiation Boundary Integration (RBI) technology to provide very consistent, wide coverage. 120° conical coverage. 6" LF driver with silk-dome tweeter for extended bass and hi-fidelity performance. 75 watts. 8 ohms and 60W multi-tap transformer. Avail. in black or white.
	JBL1094	CONTROL 67P/T
	JBL1095	CONTROL 67P/T WH
		Control 67HC/T Narrow coverage high-ceiling pendant speaker. Ideal for improved voice intelligibility and musical clarity in high ceiling venues or in rooms with difficult acoustics.. 75° conical coverage. 6" LF driver with silk-dome tweeter for extended bass and hi-fidelity performance. High 93dB sensitivity. 75 watts. 8 ohms and 60W multi-tap transformer. Available in black or white.
	JBL1096	CONTROL 67HC/T
	JBL1097	CONTROL 67HC/T WH
		MTC-PC60 Terminal cover for Control 65P/T, Control 67P/T and Control 67HC/T
	JBL1273	MTC-PC60
		MTC-PC62 Terminal cover for Control 62P
	JBL1274	MTC-PC62

PRODUCT	PRODUCT REF	DESCRIPTION
CBT SERIES		
		CBT 50LA-1 50cm Constant Beamwidth Technology™ line array column speaker. 8x2" drivers. 20° vertical, 150° horizontal coverage. 93dB sensitivity. Music/speech switch. 60W multi-tap transformer or 8 ohms. 80Hz-20kHz frequency response. 150W continuous power handling, 8Ω. New -1 version has pan/tilt wall bracket and thicker, stronger grille. Black or white.
	JBL1149	CBT 50LA-1
	JBL1150	CBT 50LA-1-WH
		CBT 100LA-1 100cm Constant Beamwidth Technology™ line array column speaker. 16x2" drivers. Switchable 40° or 15° vertical coverage, 150° horizontal. Music/speech switch. 100W multi-tap transformer or 8 ohms. 80Hz-20kHz frequency response. 325W continuous power handling, 8Ω. 96dB sensitivity. New -1 version has pan/tilt wall bracket and thicker, stronger grille. Black or white.
	JBL1151	CBT 100LA-1
	JBL1152	CBT 100LA-1-WH
		CBT 70J-1 70cm J-shaped coaxial line array with Constant Beamwidth Technology™ and asymmetrical coverage. 16x1" and 4x5" drivers. Switchable 40° or 25° vertical coverage, 150° horizontal. Music/speech switch. 60Hz-20kHz frequency response. 500W continuous power handling, 8Ω. New -1 version has pan/tilt wall bracket and thicker, stronger grille. Black or white.
	JBL1153	CBT 70J-1
	JBL1154	CBT 70J-1-WH
		CBT 70JE-1 70cm extension for CBT70J. 4x5" drivers. 8 ohms. 500W continuous power handling. 90dB sensitivity. Combined with CBT70J, system response is 45-20kHz with pattern control to 400Hz. New -1 version has pan/tilt wall bracket and thicker, stronger grille. Black or white.
	JBL1155	CBT 70JE-1
	JBL1156	CBT 70JE-1-WH

PRODUCT	PRODUCT REF	DESCRIPTION
CBT SERIES		
		CBT 200LA-1 Patented Constant Beamwidth Technology™ provides true wide-band constant directivity coverage up to the highest frequencies and reduces out-of-coverage lobing. 200 cm height extends pattern control to include lower frequencies. 32 2" full range drivers. 130Hz-18kHz (±3dB) Vertical pattern coverage switchable between 30° and 15°. 150° horizontal. 650W (2hrs), 123dB max SPL. Built-in 70/100v transformer or 8Ω. Pan/tilt bracket included. Black or white.
	JBL1209	CBT 200LA-1
	JBL1210	CBT 200LA-1-WH
		MTC-CBT-SMB1 Stand mount bracket for CBT Series speakers
	JBL0932	MTC-CBT-SMB1
		MTC-CBT-FM1 Flush-mount bracket for CBT50 and CBT100. Available in black or white.
	JBL1157	MTC-CBT-FM1
	JBL1158	MTC-CBT-FM1-WH
		MTC-CBT-FM2 Flush-mount bracket for CBT70J and CBT70JE. Available in black or white.
	JBL1159	MTC-CBT-FM2
	JBL1160	MTC-CBT-FM2-WH
		MTC-CBT-70T Transformer kit for CBT70J-1 or CBT70J-1/CBT70JE-1 systems. Taps at 120W, 60W, 30W and 15W (70v only). IP55 rated, moisture and salt-spray resistant.
	JBL1130	MTC-CBT-70T
CONTROL CRV		
		Control CRV Unique contemporary curved design, combinable into 180°, 270° or 360° round arc clusters. Selectable 70/100V or 4 ohm. 80Hz-20kHz frequency response. 75W continuous handling. Indoor/outdoor capable. Wall mount bracket included. Black or white.
	JBL0884	CONTROL CRV
	JBL0885	CONTROL CRV WH

PRODUCT	PRODUCT REF	DESCRIPTION
		CONTROL CRV
		PMB-BK Pole mount bracket for combining four Control CRV into a 360° cluster for attachment via fan pole. Black or white.
	JBL0886	PMB-BK
	JBL0887	PMB-BK WH
		CONTROL SERIES
		Control 1 PRO Two-way compact monitor. 150W continuous power handling. 5.25" low frequency driver, 1/4" HF driver. Professional drivers and crossover network. Magnetically shielded. SonicGuard overload protection. Black or white. Priced individually, but sold in pairs only.
	JBL0721	CONTROL 1 PRO
	JBL0722	CONTROL 1 PRO WH
		Control 2P Compact Powered Reference Monitors. Ideal for desktop recording, video production, AV presentations, broadcast applications and monitoring of electronic musical instruments. 5.25" driver and 1/4" dome tweeter. 2x35W amplifier. XLR, jack and phono inputs. Volume control, headphone jack and HF contour control. Master speaker also available separately.
	JBL0796	CONTROL 2 P
	JBL0797	CONTROL 2 P MASTER ONLY
		MTC-2P Wall mount kit for Control 2P.
	JBL0798	MTC-2P
		Control 5 Compact two-way loudspeaker. 6.5" LF driver, 1" titanium dome tweeter. Molded enclosure, shielded magnet. Black or white.
	JBL0118	CONTROL 5
	JBL0119	CONTROL 5 WH

PRODUCT	PRODUCT REF	DESCRIPTION
AE SERIES - ALL WEATHER COMPACT		
		AWC82 Compact, coaxial driver, two highly weather resistant full range loudspeaker system. 8" woofer with Kevlar-reinforced cone and 2" voice coil. 1" exit compression driver with unique patented design and high temperature polymer diaphragm. Consistent 120° x 120° broadband pattern control. 250W continuous, 118dB max SPL. 200W 70/100v multi-tap transformer or 8Ω. IP56 weather rating. Grey or black. U-bracket included.
	JBL1211	AWC82
	JBL1212	AWC82-BK
		AWC129 Compact, coaxial driver, two highly weather resistant full range loudspeaker system. 12" woofer with Kevlar-reinforced cone and 3" voice coil. 1" exit compression driver with unique patented design and high temperature polymer diaphragm. Consistent 90° x 90° broadband pattern control. 400W continuous, 122dB max SPL. 200W 70/100v multi-tap transformer or 8Ω. IP56 weather rating. Grey or black. U-bracket included.
	JBL1213	AWC129
	JBL1214	AWC129-BK
		AW266 High power, lightweight, 2-way, full-range loudspeaker. 12" Differential Drive LF, 3" voice coil compression driver. 60° x 60° PT waveguide. 500W continuous. 8Ω, 98dB sensitivity. 400W 70/100V transformer included. Heavily braced fibreglass enclosure with 14 gauge stainless steel grille backed with open cell foam and stainless steel mesh provides excellent protection in the harshest environments. Stainless steel U-type mounting bracket included. Available in grey or black finish.
	JBL1185	AW266
	JBL1186	AW266-BK
		AW295 As above but with 90° x 50° rotatable waveguide.
	JBL1187	AW295
	JBL1188	AW295-BK

PRODUCT	PRODUCT REF	DESCRIPTION
AE SERIES - ALL WEATHER COMPACT		
		AW526 High power, lightweight, 2-way, full-range loudspeaker. 15" Differential Drive LF, 3" voice coil compression driver. 120° x 60° rotatable PT waveguide. 600W continuous, 8Ω. 99dB sensitivity. 400W 70/100V transformer included. Heavily braced fibreglass enclosure with 14 gauge stainless steel grille backed with open cell foam and stainless steel mesh provides excellent protection in the harshest environments. Stainless steel U-type mounting bkt. included. Avail. in grey or black finish.
	JBL1189	AW526
	JBL1190	AW526-BK
		AW566 As above but with 60° x 60° waveguide.
	JBL1191	AW566
	JBL1192	AW566-BK
		AW595 As above but with 90° x 50° rotatable waveguide.
	JBL1193	AW595
	JBL1194	AW595-BK
VRX900 SERIES		
		VRX928LA Lightweight (13kg) two-way constant curvature array system. 8" Differential Drive woofer, two neodymium HF compression drivers. Passive or bi-amp modes. Speakon inputs. Duraflex coated ply cabinet. 35 mm dual-angle pole mount & internal rigging hardware. 800W, continuous, 8Ω. Passive sensitivity 90dB. Max SPL 122dB. Also available in white.
	JBL0742	VRX928LA
	JBL0805	VRX928LA-WH
	GAT0058	VRX928LA-CVR
	GAT0057	VRX928LA-BAG
		VRX932LA-1 Two-way constant curvature array system. 12" Differential Drive woofer, two neodymium HF compression drivers. Passive or bi-amp modes. Speakon inputs. Duraflex coated ply cabinet. 35 mm dual-angle pole mount & internal rigging hardware. 800W continuous. Passive sensitivity 95dB max SPL 130dB. Also available in white.
	JBL0609	VRX932LA-1
	JBL0658	VRX932LA-1-WH
	GAT0059	VRX932LA-1-CVR
	GAT0043	VRX932LA-1-BAG

PRODUCT	PRODUCT REF	DESCRIPTION
VRX900 SERIES		
		VRX932LAP Powered array system. As 932LA-1 but with built-in JBL/Crown DrivePack DPC2 amplifier module. 875W continuous. Max SPL 136dB.
	JBL0755	VRX932LAP
	GAT0060	VRX932LAP-BAG
	GAT0061	VRX932LAP-CVR
		VRX915S 15" Bass reflex subwoofer. Differential Driver woofer. Passive or bi-amp operation. Duraflex coated 15/18mm ply enclosure. 20mm threaded pole socket. Internal rigging hardware for connecting to VRX928 units. 800W continuous. Passive sensitivity 91dB. Max SPL 126dB. Also available in white.
	JBL0741	VRX915S
	JBL0806	VRX915S-WH
	GAT0054	VRX915S-CVR
	GAT0055	VRX915S-STR
		VRX918S 18" compact subwoofer for use with VRX932 units. 18" Differential Driver woofer. Duraflex coated 18mm ply enclosure. 20mm threaded pole socket. Internal rigging hardware. 800W continuous, 8Ω. Sensitivity 95dB. Max SPL 130dB. Also available in white.
	JBL0623	VRX918S
	JBL0659	VRX918S-WH
	GAT0056	VRX918S-STR
	GAT0052	VRX918S-CVR
		VRX918SP Powered subwoofer. Specs as VRX918S but with JBL/Crown DrivePack DPC-2 amplifier. 750/1500W (continuous/peak). Max SPL 126dB.
	JBL0756	VRX918SP
		VRX915M Two-way floor monitor. 15" Differential Drive woofer, 4" voice coil compression driver. Passive or bi-amp modes. Duraflex coated ply 30° wedge enclosure. 800W continuous. Passive sensitivity 98dB. 8Ω. Max SPL 127dB.
	JBL0707	VRX915M
	GAT0053	VRX915M-CVR-CXD

PRODUCT	PRODUCT REF	DESCRIPTION
VRX900 SERIES		
		VRX-SMAF Small array frame for VRX928 and VRX915S.
	JBL0740	VRX-SMAF
		VRX-AF Array frame for VRX932 and VRX918S.
	JBL0660	VRX-AF
		WK-4S Wheel kit for VRX915S, VRX918S and SRX718S. 4 swivel castors and mounting hardware.
	JBL0578	WK-4S
		SS4-BK Adjustable pole for use with VRX900.
	JBL0577	SS4-BK
		FLIGHT-SRX718S/VRX918S Flight Case for (1x) SRX718S / VRX918S. 1/2" Plywood Construction, 3.5" locking casters. Truck Pack Exterior.. Stackable.
	GAT0071	FLIGHT-SRX718S/VRX918S
STX800 SERIES		
		STX812M High performance floor monitor which can double as a utility speaker. Compact and low-profile for minimal obstruction of audience sight-lines. High power handling, low distortion 12" Vented Gap Cooling™ LF driver. 3" diaphragm neodymium magnet compression driver. 1600W continuous. Sensitivity 95dB. 130dB SPL peak, 8Ω. 75Hz-20kHz ±3dB. 70°x 70° nominal coverage. Bi-amplified or full-range passive operation. Pole socket for applications requiring pole or tripod mounting.
	JBL1200	STX812M
	GAT0079	STX812M-CVR
		STX815M A single 15" lightweight two-way system designed to function as a high-power handling, FOH loudspeaker system or as an extended range floor monitor. High power handling, low distortion 15" Vented Gap Cooling™ LF driver. 3" diaphragm neodymium magnet compression driver. 1600W continuous. Sensitivity 96dB. 131dB SPL peak, 8Ω. 55Hz-20kHz ±3dB. 70°x 70° nominal coverage. Bi-amplified or full-range passive operation. Pole socket for applications requiring pole or tripod mounting. Twelve M10 suspension points.
	JBL1201	STX815M
	GAT0080	STX815M-CVR

PRODUCT	PRODUCT REF	DESCRIPTION
STX800 SERIES		
		STX825 A dual 15" two-way speaker designed for maximum impact, portability and ease of use. Ideal for bands or DJ's as their primary PA, use as a side-fill on a concert stage, or as an install speaker in a dance club or performance venue. Compact and very high-power. Two low distortion 15" Vented Gap Cooling™ LF drivers. 4" diaphragm neodymium magnet compression driver. 3200W continuous. Sensitivity 98dB. 136dB SPL peak, 4Ω. 42Hz-19kHz ±3dB. 90°x 50° nominal coverage. Bi-amplified or full-range passive operation. Twelve M10 suspension points.
	JBL1202	STX825
	GAT0082	STX825-CVR
		STX835 A slot-loaded dual 15" three-way system with horn-loaded mid and high sections, designed for full-range use in stand-alone applications or for use in high performance environments as the premier ground stack passive top box. Designed to be placed over the STX828S, this cabinet can be used in multiples in a high density situation. 15" Vented Gap Cooling™ LF driver., 8" CMCD™ Cone Midrange Compression Driver. 4" diaphragm neodymium magnet compression driver. 3200W continuous. Sensitivity 96dB. 134dB SPL peak, 4Ω. 43Hz-20kHz ±3dB. 60°x 40° nominal coverage. Bi-amplified or full-range passive operation.
	JBL1203	STX835
	GAT0084	STX835-CVR
		STX818S A single 18" compact high power subwoofer system in a front-loaded, vented enclosure designed for minimum frontal area provides 1,000 watts of continuous pink noise power handling. 18" Super Vented Gap™ woofer for extended low-frequency output. Large port area for reduced distortion. Sensitivity 96dB. 132dB SPL peak. 8Ω. 40Hz-120Hz ±3dB. 20 mm threaded pole socket for solid, secure satellite speaker mounting.
	JBL1204	STX818S
	GAT0081	STX818S-CVR

PRODUCT	PRODUCT REF	DESCRIPTION
STX800 SERIES		
		STX828S A dual 18" high power subwoofer system in a front-loaded, vented enclosure designed for maximum low-frequency performance. Two drivers give 2,000 watts of continuous pink noise power handling, 4kW program and 8 kW peak. Dual 18" Super Vented Gap™ woofers for extended low frequency output. 138dB SPL peak. Sensitivity 99dB. 4Ω. 37Hz-120Hz ±3dB.
	JBL1205	STX828S
	GAT0083	STX828S-CVR
PRX700 SERIES		
		PRX710 10" two-way multipurpose self-powered loudspeaker. 1.5" Annular Polymer diaphragm, 10" Differential Drive woofer. 1500W Class-D amplifier. 60°x100° coverage. Max SPL 133dB. Frequency response (±3dB) 63.5Hz - 18.5kHz. Two channel input mixer with XLR and RCA inputs, integrated limiter, crossover and selectable system EQ. 25/18mm plywood cabinet with JBL DuraFlex finish, 16 gauge steel grille. M10 suspension points. Weight 16.4kg.
	JBL1359	PRX710
		PRX712 12" two-way full-range powered main system/floor monitor. 1.5" Annular Polymer diaphragm, 12" Differential Drive woofer. 1500W Class-D amplifier. 90°x50° coverage. Max SPL 135dB. Frequency response (±3dB) 55.7Hz - 18.2kHz. Two channel input mixer with XLR and RCA inputs, integrated limiter, crossover and selectable system EQ. 25/18mm plywood multi-angle cabinet with JBL DuraFlex finish, 16 gauge steel grille. M10 suspension points. Weight 19.4kg.
	JBL1360	PRX712
		PRX715 15" two-way full-range powered main system/floor monitor. 1.5" Annular Polymer diaphragm, 15" Differential Drive woofer. 1500W Class-D amplifier. 90°x50° coverage. Max SPL 136dB. Frequency response (±3dB) 58.1Hz - 17.2kHz. Two channel input mixer with XLR and RCA inputs, integrated limiter, crossover and selectable system EQ. 25/18mm plywood multi-angle cabinet with JBL DuraFlex finish, 16 gauge steel grille. M10 suspension points. Weight 21.6kg.
	JBL1361	PRX715

PRODUCT	PRODUCT REF	DESCRIPTION
PRX700 SERIES		
		PRX725 Dual 15" two-way full-range powered main system loudspeaker. 1.5" Annular Polymer diaphragm, two 15" Differential Drive woofers. 1500W Class-D amplifier. 90°x50° coverage. Max SPL 139dB. Frequency response (±3dB) 49Hz - 17kHz. Two channel input mixer with XLR and RCA inputs, integrated limiter, crossover and selectable system EQ. 25/18mm plywood multi-angle cabinet with JBL DuraFlex finish, 16 gauge steel grille. M10 suspension points. Weight 37.2kg
	JBL1362	PRX725
		PRX735 15" three-way full-range powered main system loudspeaker. 1.5" Annular Polymer diaphragm, 6.5" horn loaded midrange transducer, 15" Differential Drive woofer. 1500W Class-D amplifier. 90°x50° coverage. Max SPL 136dB. Frequency response (±3dB) 42Hz - 20kHz. Two channel input mixer with XLR and RCA inputs, integrated limiter, crossover and selectable system EQ. 25/18mm plywood multiangle cabinet with JBL DuraFlex finish, 16 gauge steel grille. M10 suspension points. Weight 34.9kg
	JBL1363	PRX735
		PRX715XLF 15" powered extended low frequency subwoofer. 15" Differential Drive woofer. 1500W Class-D amplifier. 90°x50° coverage. Max SPL 131dB. Frequency response (±3dB) 44Hz - 91Hz. Input section with integrated limiter, crossover and selectable system EQ. Pole receptacle accepts a SS4-BK or SS4-BK24. 25/18mm plywood multi-angle cabinet with JBL DuraFlex finish, 16 gauge steel grille. Weight 25.4kg
	JBL1354	PRX715XLF
		PRX718XLF 18" powered extended low frequency subwoofer. 18" Differential Drive woofer. 1500W Class-D amplifier. 90°x50° coverage. Max SPL 134dB. Frequency response (±3dB) 35Hz - 87Hz. Input section with integrated limiter, crossover and selectable system EQ. Pole receptacle accepts a SS4-BK or SS4-BK24. 25/18mm plywood multi-angle cabinet with JBL DuraFlex finish, 16 gauge steel grille. Weight 36.8kg
	JBL1365	PRX718XLF
		SS4-BK24 24" fixed length heavy duty pole for PRX715XLF and PRX718XLF speakers.
	JBL1134	SS4-BK24

PRODUCT	PRODUCT REF	DESCRIPTION
PRX400 SERIES		
		PRX412M Portable, 12" two-way speaker system. Frequency range 50Hz-19kHz. Power rating 300W continuous, 1200W peak. System sensitivity 95dB SPL 1w@1m. Max SPL 126dB peak. 8 ohm impedance. 90°x50° coverage for even and smooth response on and off axis. SonicGuard™ HF protection. Dual-angle pole socket. Heavy duty 16 gauge steel grille. 12 M10 suspension points. Tough DuraFlex™ enclosure finish. Also available in white for installation applications.
	JBL1178	PRX412M
	JBL1325	PRX412M-WH
	GAT0075	PRX412M-CVR
		PRX415M Portable, 15" two-way speaker system. Frequency range 55Hz-19kHz. Power rating 300W continuous, 1200W peak. System sensitivity 98dB SPL 1w@1m. Max SPL 129dB peak. 8 ohm impedance. 90°x50° coverage for even and smooth response on and off axis. SonicGuard™ HF protection. Dual-angle pole socket. Heavy duty 16 gauge steel grille. Tough DuraFlex™ enclosure finish. Also available in white for installation applications.
	JBL1179	PRX415M
	JBL1326	PRX415M-WH
	GAT0076	PRX415M-CVR
		PRX425 Portable, dual 15" two-way speaker system. Frequency range 55Hz-19kHz. Power rating 600W continuous, 2400W peak. System sensitivity 100dB SPL 1w@1m. Max SPL 134dB peak. 4 ohm impedance. 90°x50° coverage for even and smooth response on and off axis. SonicGuard™ HF protection. Dual-angle pole socket. Heavy duty 16 gauge steel grille. Tough DuraFlex™ enclosure finish.
	JBL1180	PRX425
	GAT0078	PRX425-CVR
		PRX418S Portable 18" subwoofer. Frequency range 35Hz-300Hz. Power rating 800W continuous, 3200W peak. System sensitivity 95dB SPL 1w@1m. Max SPL 130dB peak. 8 ohm impedance. Heavy duty 16 gauge steel grille. Tough DuraFlex™ enclosure finish.
	JBL1181	PRX418S
	GAT0077	PRX418S-CVR

PRODUCT	PRODUCT REF	DESCRIPTION
PRX200 SERIES		
		JRX212 Portable, twelve-inch, two-way speaker system designed specifically for live performance. M112-8 12" LF driver. 2414H-C 1" polymer diaphragm compression driver mounted on Progressive Transition™ Waveguide. 90° x 50° dispersion. 129dB max SPL. Power rating 250W continuous, 1000W peak. Sensitivity 99dB (1W, 1 m). 8 ohms. Attractive 18-gauge hexagon perforated, steel grille. Dual-angle polemount socket.
	JBL1351	JRX212
	GAT0010	JRX112M-CRV-CX
		JRX215 Portable, 15" two-way speaker system designed specifically for live performance. M115-8A 15" LF driver. 2414H-C 1" polymer diaphragm compression driver mounted on Progressive Transition™ Waveguide. 90° x 50° dispersion. 128dB max SPL. Power rating 250W continuous, 1000W peak. Sensitivity 98dB (1W, 1 m). 8 ohms. Attractive 18-gauge hexagon perforated, steel grille. Dual-angle polemount socket.
	JBL1352	JRX215
	GAT0011	JRX115M-CRV-CX
		JRX225 Dual, 15" two-way speaker system designed specifically for live performance. M128 15" LF drivers. 2414H-C 1" polymer diaphragm compression driver mounted on Progressive Transition™ Waveguide. 90° x 50° dispersion. 123dB max SPL. Power rating 500W continuous, 2000W peak. Sensitivity 100dB (1W, 1 m). 4 ohms. Attractive 18-gauge hexagon perforated, steel grille.
	JBL1353	JRX225
	GAT0013	JRX125-CRV-CX
		JRX218S 18" subwoofer with cast frame and 3" voice coil. JBL 2043-G driver.. 90° x 50° dispersion. 127dB max SPL. Power rating 350W continuous, 1400W peak. Sensitivity 96dB (1W, 1 m). 4 ohms. Attractive 18-gauge perforated steel grille protects components from damage. Top mounted, cast aluminum 35 mm pole mount receptacle.
	JBL1354	JRX218S
	GAT0012	JRX118S-CRV-CX