



**NEUTRIK**











**F**  **OLEY** **SOUND**  
engineering

40 Sycamore Road,  
Rathnash,  
Carlow,  
Ireland.

Tel: 059 9131725  
M: 087 9894696

[www.foleysoundengineering.com](http://www.foleysoundengineering.com)  
[info@foleysoundengineering.com](mailto:info@foleysoundengineering.com)

PRODUCT	PRODUCT REF	DESCRIPTION
<b>3 POLE XLR CONNECTORS</b>		
	NC3FXX	3 pole line female XX series XLR.
	NC3MXX	3 pole line male XX series XLR.
	NC3FM-C	3 pole unisex XLR connector. Easily selectable gender, converted by sliding housing back and forth.
	NC3FRX	3 pole line female right-angle XLR.
	NC3MRX	3 pole line male right-angle XLR.
	NC3FRC	3 pole line female compact right-angle XLR.
	NC3MRC	3 pole line male compact right-angle XLR.
	NC3FDLX	3 pole chassis female XLR. New DLX Series.
	NC3FD-L-1	3 pole female receptacle
	NC3MD-L-1	3 pole Male receptacle
	NC3MDLXB LI	3 pole chassis male XLR. New DLX Series.
	NA2F-DOB-TX	Miniature transformer balancing adapter
	NSB1B-8/O	<b>STAGE BOX</b> Width: 117 mm, height: 79 mm, length: 132 mm 8 IN (Female/Send)

PRODUCT	PRODUCT REF	DESCRIPTION
<b>5 POLE XLR CONNECTORS</b>		
	NC5FXX	5 pole line female XX series XLR.
	NC5FDLX	5 pole chassis female XLR. New DLX Series.
	NC5MXX	5 pole line male XX series XLR.
	NC5MDLX	5 pole chassis male XLR. New DLX Series.
<b>ACCESSORIES FOR XLR CONNECTORS</b>		
	SCDR	Soft plastic cover for the rear of D-series chassis connectors
<b>SPEAKON CONNECTORS</b>		
	NL2FC	2 pole latching line speakon (mates with NL4MP)
	NL4FX	4 pole line female speakon.
	NL4MP	4 pole chassis male speakon with D size mounting.
	NL4MMX	4 pole latching male in-line coupler.
	NL8FC	8 pole latching line female speakon

PRODUCT	PRODUCT REF	DESCRIPTION
<b>SPEAKON CONNECTORS</b>		
	NL8MM	8 pole latching male in-line coupler
<b>POWERCON CONNECTORS</b>		
	NAC3FCA	Powercon cable connector A - Type for power in
	NAC3FCB	Powercon cable connector B - Type for power out
	NAC3MPA	Powercon air tight chassis connector A - Type for power in Flat tab terminals
<b>MONO JACK CONNECTORS</b>		
	NP2RX	1/4 inch right angle mono jack plug.
	NP2X	1/4 inch ultra-slim mono jack plug. All metal, no rivets
<b>STEREO JACK CONNECTORS</b>		
	NP3X	1/4 inch ultra-slim stereo jack plug. All metal, no rivets
	NP3RX	1/4 inch right angle stereo jack plug with nickel shell and nickel contacts.
	NJ3FP6C	1/4 inch chassis locking jack socket.

PRODUCT	PRODUCT REF	DESCRIPTION
<b>PHONO CONNECTORS</b>		
	NYS373-0	Phono plug with gold plated contacts and black marker ring
	NYS373-2	Phono plug with gold plated contacts and red marker ring.
	NYS373-4	Phono plug with gold plated contacts and yellow marker ring
<b>PHONO CONNECTORS</b>		
	NF2D-0	Phono socket with D size mounting. Black.
	NF2D-2	Phono socket with D size mounting. Red.
	NF2D-4	Phono socket with D size mounting. Yellow
<b>BANANA CONNECTORS</b>		
	NYS508-B	Dual Banana Plug, black, teathed cable clamp, protection against electric shock: cable ends and plugs are completely covered in mated condition
	NYS508-R	Dual Banana Plug, red, teathed cable clamp, protection against electric shock: cable ends and plugs are completely covered in mated condition
<b>REAN CONNECTORS</b>		
	RT3FC-B	3-pole TINY cable connector, black metal shell, gold plated contacts, Industrial bulk packaging (AKG TYPE)
	RT4FC-B	4-pole TINY cable connector, black metal shell, water resistant due to rubber sealing boot (patent pending), gold plated contacts, Industrial bulk packaging (SHURE TYPE)